

Bunded Tanks



1200 CBS Slimline - 160KG
Dimensions - Length - 1880mm
Width - 880mm
Height - 1700mm
Capacity - 1200 Litres
264 Gallons
Footprint - Length - 1880mm
Width - 880mm



1000 OTBS SUPER SPACE SAVER - 128KG
Dimensions - Length - 1830mm
Width - 610mm
Height - 1580mm
Capacity - 1000 Litres
220 Gallons
Footprint - Length - 1830mm
Width - 610mm



1350 CBH - 155KG
Dimensions - Length - 1845mm
Width - 1246mm
Height - 1540mm
Capacity - 1350 Litres
296 Gallons
Footprint - Length - 1845mm
Width - 1246mm



2400 CBFT - 220KG
Dimensions - Length - 2250mm
Width - 1450mm
Height - 1635mm
Capacity - 2468 Litres
543 Gallons
Footprint - Length - 2250mm
Width - 1450mm



5000 CBV - 280KG
Dimensions - Diameter - 2000mm
Height - 2400mm
Capacity - 5000 Litres
2000 Gallons
Footprint - Diameter - 2000mm



1200CS - 80KG
Dimensions - Length - 1820mm
Width - 680mm
Height - 1410mm
Capacity - 1200 Litres
264 Gallons
Footprint - Length - 1700mm
Width - 620mm



2400CH - 100KG
Dimensions - Length - 2050mm
Width - 1330mm
Height - 1355mm
Capacity - 2468 Litres
543 Gallons
Footprint - Length - 1640mm
Width - 1230mm



1350CH - 75KG
Dimensions - Length - 1720mm
Width - 1130mm
Height - 1110mm
Capacity - 1350 Litres
296 Gallons
Footprint - Length - 1345mm
Width - 1035mm



5000CV - 130KG
Dimensions - Diameter - 1900mm
Height - 2250mm
Capacity - 5000 Litres
2000 Gallons
Footprint - Diameter - 1900mm

ACCESSORIES

Pus Tank Installation Kit

Installation kit comes with filter bowl and lever valve, a roll of PTFE and a reducer.



Ultrasonic Gauge

Uses a transmitter on top of the tank and ultrasonic level measurement techniques to measure, continually, the level of an oil tank.



Premium Fuel Stations

Both 1350CFC and the 2400CFC come with auto shut off, 4 meter hose, flowmeter and 10 micron filter. 230v as standard. 12v and 24v optional. 4m hose as standard.



1350CFC - 175KG

Dimensions - Length - 1845mm
Width - 1246mm
Height - 1540mm

Capacity - 1350 Litres
296 Gallons

Footprint - Length - 1845mm
Width - 1246mm



2400CFC - 240KG

Dimensions - Length - 2250mm
Width - 1520mm
Height - 1740mm

Capacity - 2468 Litres
543 Gallons

Footprint - Length - 2250mm
Width - 1520mm



5000CFC - 380KG

Dimensions - Length - 2000mm
Height - 2400mm

Capacity - 5000 Litres
2000 Gallons

Cabinet - Width - 1100mm
Depth - 750mm
Height - 2000mm

Footprint - Diameter - 2750mm

The 5000CFC comes with auto shut off, 4 meter hose, flowmeter and 10 micron filter. 230v as standard. 12v & 24v optional. 4m hose as standard. Also includes overfill prevention, strong bulk internal light for night filling & Unitop mechanical tank level gauge calibrated by %.

Both 1350CFC & the 2400CFC come with auto shut off, 4 meter hose & 10 micron filter. 230v as standard. 12v & 24v optional. 4m hose as standard.

Standard Fuel Stations



1350CFC Standard - 175KG

Dimensions - Length - 1845mm
Width - 1246mm
Height - 1540mm

Capacity - 1350 Litres
296 Gallons

Footprint - Length - 1845mm
Width - 1246mm



2400CFC Standard - 240KG

Dimensions - Length - 2250mm
Width - 1520mm
Height - 1740mm

Capacity - 2468 Litres
543 Gallons

Footprint - Length - 2250mm
Width - 1520mm